



VRIJSTAANDE DIGITALE POSTER OUTDOOR

Outdoor Freestanding Digital Posters

49" | 55"



Direct Sunlight Readable

Designed for the challenge of direct sunlight, these displays use commercial grade ultra high brightness panels (2,500 cd/m²); up to 10 times brighter than a domestic television.



2,500cd/m²

Vandalproof

The enclosure is made from mild steel as well as having a thermally toughened glass front. Controls and inputs are also hidden and not accessible to passers-by to avoid tampering.



5mm Tough Glass



Weatherproof


Designed with a robust, corrosion protected, outer casing to give protection from the elements. The outer casing has an IP65 rating which means it keeps out airborne swarf, dust and other particles as well as being protected from any wet weather conditions.



Protection from the weather!

Advanced Temperature Control System

The internal airflow system keeps your screen running at the optimal temperature regardless of the external conditions to maximise the life of your product. Built in air-conditioning can be tailored to allow the display to work in any climate.



50°

-20°

Operating Temperature

Key Features



2,500 CD/M²
SUNLIGHT READABLE




WEATHER PROOF



AMBIENT LIGHT SENSOR




ANTI-REFLECTIVE GLASS



VANDAL PROOF




DUST TIGHT




PLUG AND PLAY



MODIFICATIONS




2,500cd/m²
DIRECT SUNLIGHT
READABLE



IP65

IP65 RATED ENCLOSURE



TEMPERATURE CONTROL



REMOVABLE BASE

Other Features

IP65 Rated Sturdy Enclosure

An IP65 rating means that display is able to withstand all wet weather conditions and also keeps out airborne dust.

IP65

- Dust Resistance**
6 Protected against dust that may harm equipment.
- Water Resistance**
5 Protected against water spray from all directions.



Anti Reflective Glass

The front glass face is specially treated which helps to diffuse direct sunlight making the display easily readable in bright weather conditions.



Ambient Light Sensor

The display has a light sensor that changes the screen's brightness depending on the ambient light ensuring the most suitable brightness at any time of the day.



Optional Network Upgrade

For a small charge you can upgrade your screen to be networked, allowing you to connect your screen via Wi-Fi, LAN or 4G, then remotely update it over the internet. For more information please go to page 91.



Easy Maintenance

The screen is designed to allow for easy front access using hydraulic cylinders when maintenance is required.



Plug and Play

Plug and Play is the most straightforward way to upload content to the screen. Simply load images and videos onto a USB stick, insert into the display, wait for your content to copy over and then remove. Your images and videos will now play in a continuous loop.



Internal Locker

Should you need connect the screen to an external source, like a PC or media player, you can use the HDMI input or the VGA and 3.5mm audio jack inputs and hide the player inside the internal locker.



Hardware Modifications

These displays can be adapted in a variety of ways including a touch screen upgrade and the integration of a 4G module or camera.



	49 Inch	55 Inch
Panel	Resolution	1920x1080
	Pixel Pitch	0.5592 x 0.5592
	Display Area (mm)	610x1079.8
	Aspect Ratio	16:9
	Brightness (cd/m²)	2,500
	Colour	1.06 B
	Viewing Angle	178°
AV Inputs	Contrast Ratio	8000:1
	Video	HDMI, VGA
Power	Power Consumption (W)	300
	Input Voltage	AC110~240V (50Hz~60Hz)
Mechanical	Unit Size (WxHxD mm)	870x1950x197
	Package Size (WxHxD mm)	2030x993x368
	Footprint (WxHxD mm)	890x500
	Net Weight (kg)	120
	Gross Weight (kg)	147
Environmental	IK Rating	IK08
	Operating Temperature:	-20 °C to 50 °C
	Operating Humidity:	10% - 80%
	Storage Temperature:	-30°C - 60°C
	Storage Humidity:	5% - 90%
Computer	Enclosure Protection	IP65
	Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)
	Media Resolution	1920x1080/1080x1920
	Internal Memory	6GB
	CPU	Quad-Core Cortex-A17@1.61GHz
	GPU	Mali-T760 MP4 @600MHz
	RAM	2GB DDR3
	ROM	8GB NAND
	USB	USB2.0 HOST (x2)
	LAN	10/100M Ethernet (Network Version Only)
	Wi-Fi	802.11b/g/n/ac (Network Version Only)
	OS	Android 5.1.1
Accessories	Graphic Engine	OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1
	Included	AC Power Cable, Remote Control
Warranty	Optional	Touch Screen Upgrade, Network Upgrade, Camera
	Warranty Period	3 Year Warranty
	Technical Support	Lifetime





NEEM CONTACT OP.

WE KIJKEN GRAAG WAT WE VOOR UW ONDERNEMING KUNNEN BETEKENEN

Met ons grote assortiment aan Digital Signage producten, communiceert en informeert u makkelijker met uw klanten of medewerkers op een moderne en digitale manier.

ProDigit

Impact 35

6921 RZ Duiven

Telefoonnummer: +31 6 83796776

E-mail: sales@pro-digit.nl